

# Two-echelon capacitated vehicle routing problem with time-windows

Guillaume Marques<sup>1,2,3</sup>, Ruslan Sadykov<sup>2,3</sup>, Jean-Christophe Deschamps<sup>1</sup>, Rémy Dupas<sup>1</sup>

<sup>1</sup> Université de Bordeaux, IMS, UMR 5218

{jean-christophe.deschamps, remy.dupas}@ims-bordeaux.fr

<sup>2</sup> RealOpt Inria Bordeaux Sud-Ouest, France

{guillaume.marques, ruslan.sadykov}@inria.fr

<sup>3</sup> Université de Bordeaux, IMB, UMR 5251

**Mots-clés :** *two-echelon vehicle routing, exact approach, column and cut generation, synchronization*

## Abstract

In a two-level distribution system with time windows, the first level involves trucks that ships goods from a distribution center to intermediate depots called satellites. The second level involves city freighters that are loaded with goods at satellites and deliver the customers. Each customer must be visited once and within its time-window. The two-echelon capacitated vehicle routing problem with time windows aims to minimise the total transportation cost in such a distribution system. Two quite similar variants of this problem have been treated in the literature. One variant [1] assuming that city freighters receive goods from only one urban truck is solved using an exact method. A second variant [2] assuming that city freighters do multi-trips is solved with a heuristic approach.

We present a path-based formulation for this problem where synchronisation constraints ensure that first-level routes deliver enough items before the departure of second-level routes. First-level routes and second-level routes are generated by pricing problems. Synchronisation constraints are separated because they are many of them. We tackle the problem with a branch-and-cut-and-price algorithm that uses significant improvements recently proposed in the literature for the standard vehicle routing problems [3]. We compare such algorithm and results with the two similar variants proposed in the literature.

## Références

- [1] Nico Dellaert, Fardin Dashty Saridarq, Tom Van Woensel, and Teodor Gabriel Crainic. Branch-and-price-based algorithms for the two-echelon vehicle routing problem with time windows. *Transportation Science*, 53(2) :463–479, 2018.
- [2] Philippe Grangier, Michel Gendreau, Fabien Lehuédé, and Louis-Martin Rousseau. An adaptive large neighborhood search for the two-echelon multiple-trip vehicle routing problem with satellite synchronization. *European Journal of Operational Research*, 254(1) :80–91, 2016.
- [3] Artur Pessoa, Ruslan Sadykov, Eduardo Uchoa, and François Vanderbeck. A generic exact solver for vehicle routing and related problems. In *International Conference on Integer Programming and Combinatorial Optimization*, pages 354–369. Springer, 2019.